

オーステナイト系

# SUS304


▶ 比重 7.93

SUS304はオーステナイト系の代表的なステンレス鋼です。ステンレスの中で最も多方面に使われている一般的なステンレス鋼で、機械的性質・耐食性に優れております。板・パイプ・アングル・丸棒など様々な形状が造られ、家庭用品から工業用品まで広範囲にわたり使われております。

オーステナイト系



# SUS304 平角棒



各種サイズ			表面状態				備考
寸法 (a × b mm)		長さ (mm)	HOT	COLD	HL	400番研磨	
2.0	× 6.0	2,000 / 4,000		◇			
	× 8.0	2,000		◇			
	× 9.0	2,000 / 4,000		◇			
	× 10.0	3,000 / 4,000	◇	◇			2,000=COLD 有り
	× 12.0	4,000		◇			
	× 15.0		◇	◇			
	× 20.0		◇	◇			
	× 25.0		◇	◇			
	× 30.0		◇	◇			
	× 32.0		◇	◇			
	× 35.0		◇				
	× 38.0		◇	◇			
	× 40.0		◇	◇			
	× 45.0		◇	◇			
× 50.0	◇	◇					
3.0	× 5.0	2,000 / 3,000		◇			
	× 6.0	4,000		◇			
	× 7.0			◇			
	× 8.0			◇			
	× 9.0			◇			
	× 10.0		◇	◇	◇		
	× 12.0		◇	◇	◇		
	× 13.0		◇	◇	◇		
	× 15.0		◇	◇	◇	◇	
	× 16.0		◇	◇	◇		
	× 19.0		◇	◇	◇		
	× 20.0	◇	◇	◇	◇		
	× 22.0	◇	◇	◇			
	× 25.0	◇	◇	◇	◇		
	× 30.0	◇	◇	◇	◇		
	× 32.0	◇	◇	◇	◇		
	× 35.0	◇	◇	◇			
	× 38.0	◇	◇	◇	◇		
	× 40.0	◇	◇	◇	◇		
	× 42.0		◇	◇			
	× 45.0	◇	◇	◇			
	× 48.0		◇	◇			
	× 50.0	◇	◇	◇	◇		
	× 60.0	◇	◇	◇	◇		
	× 65.0	◇	◇	◇			
	× 75.0	◇	◇	◇			
× 90.0	◇	◇	◇				
×100.0	◇	◇	◇				
×110.0		◇					
×120.0		◇					
×125.0		◇					
×130.0		◇					

SUS304 平角棒

各種サイズ		長さ (mm)	表面状態				備考
寸法 (a × b mm)			HOT	COLD	HL	400番研磨	
3.0	×140.0	4,000		◇			
	×150.0			◇			
4.0	× 9.0			◇			
	× 10.0			◇	◇		
	× 11.0	◇	◇	◇			
	× 12.0		◇				
	× 13.0	◇	◇	◇			
	× 15.0	◇	◇	◇	◇		
	× 16.0	◇	◇	◇			
	× 17.0		◇				
	× 19.0	◇	◇	◇			
	× 20.0	◇	◇	◇	◇		
	× 22.0	◇	◇	◇			
	× 25.0	◇	◇	◇	◇		
	× 30.0	◇	◇	◇	◇		
	× 32.0	◇	◇	◇	◇		
	× 35.0	◇	◇	◇			
	× 38.0	◇	◇	◇	◇		
	× 40.0	◇	◇	◇	◇		
	× 45.0	◇	◇	◇			
	× 50.0	◇	◇	◇	◇		
	5.0	× 8.0			◇		
× 9.0				◇			
× 10.0				◇	◇		
× 12.0				◇	◇		
× 13.0				◇	◇		
× 15.0		◇	◇	◇	◇		
× 16.0			◇	◇			
× 19.0		◇	◇	◇			
× 20.0		◇	◇	◇	◇		
× 22.0		◇	◇	◇			
× 25.0		◇	◇	◇	◇		
× 30.0		◇	◇	◇	◇		
× 32.0		◇	◇	◇	◇		
× 34.0			◇	◇			
× 35.0		◇	◇	◇			
× 38.0		◇	◇	◇	◇		
× 40.0		◇	◇	◇	◇		
× 45.0		◇					
× 50.0		◇	◇	◇	◇		
× 60.0		◇	◇	◇			
× 65.0	◇	◇	◇				
× 75.0	◇	◇	◇				
× 90.0	◇	◇	◇				

SUS304 平角棒

各種サイズ			表面状態				備考
寸法 ( a × b mm )		長さ (mm)	HOT	COLD	HL	400番研磨	
5.0	×100.0	4,000	◇	◇	◇		
	×130.0			◇			
	×150.0			◇	◇		
6.0	× 9.0			◇			
	× 10.0			◇	◇		
	× 12.0			◇	◇		
	× 13.0				◇	◇	
	× 15.0			◇	◇	◇	◇
	× 16.0				◇	◇	
	× 18.0				◇	◇	
	× 19.0			◇	◇	◇	
	× 20.0			◇	◇	◇	◇
	× 22.0			◇	◇	◇	
	× 25.0			◇	◇	◇	◇
	× 30.0			◇	◇	◇	◇
	× 32.0			◇	◇	◇	◇
	× 35.0			◇	◇	◇	
	× 38.0			◇	◇	◇	◇
	× 40.0			◇	◇	◇	◇
	× 42.0				◇	◇	
	× 45.0				◇	◇	◇
	× 48.0				◇	◇	◇
	× 50.0				◇	◇	◇
	× 50.0		6,000		◇	◇	◇
	× 60.0		4,000		◇	◇	◇
	× 65.0				◇	◇	◇
	× 65.0		6,000		◇	◇	◇
	× 70.0		4,000		◇	◇	◇
	× 75.0				◇	◇	◇
	× 75.0		6,000		◇	◇	◇
× 90.0	4,000		◇	◇	◇		
×100.0			◇	◇	◇		
×100.0	6,000		◇	◇	◇		
×110.0	4,000		◇	◇	◇		
×120.0			◇	◇	◇		
×125.0			◇	◇	◇		
×130.0			◇	◇	◇		
×140.0			◇	◇	◇		
×150.0			◇	◇	◇		
7.0	× 20.0		◇				
8.0	× 10.0			◇	◇		
	× 16.0		◇	◇	◇		
	× 25.0		◇				
	× 30.0		◇				
	× 32.0		◇	◇	◇		
	× 35.0		◇				
	× 38.0		◇	◇	◇		
	× 40.0		◇	◇			
	× 45.0		◇	◇			

SUS304 平角棒

各種サイズ		表面状態				備考
寸法 (a × b mm)	長さ (mm)	HOT	COLD	HL	400番研磨	
8.0	× 50.0	4,000	◇	◇	◇	
	× 65.0		◇	◇		
	× 75.0		◇	◇		
	× 100.0		◇	◇		
9.0	× 13.0		◇	◇	◇	
	× 15.0		◇	◇	◇	
	× 16.0		◇	◇	◇	
	× 19.0		◇	◇	◇	
	× 20.0		◇	◇	◇	◇
	× 22.0		◇	◇	◇	
	× 25.0		◇	◇	◇	◇
	× 25.0	6,000		◇	◇	
	× 30.0	4,000	◇	◇	◇	◇
	× 30.0	6,000		◇	◇	
	× 32.0	4,000	◇	◇	◇	◇
	× 32.0	6,000		◇	◇	
	× 35.0	4,000	◇	◇		
	× 38.0		◇	◇	◇	◇
	× 38.0	6,000	◇	◇	◇	
	× 40.0	4,000	◇	◇	◇	◇
	× 40.0	6,000		◇	◇	
	× 45.0	4,000	◇	◇		
	× 50.0		◇	◇	◇	◇
	× 50.0	6,000	◇	◇	◇	
	× 55.0	4,000	◇			
	× 60.0		◇	◇	◇	
	× 65.0		◇	◇	◇	◇
	× 65.0	6,000	◇	◇	◇	
	× 75.0	4,000	◇	◇	◇	◇
	× 75.0	6,000	◇	◇	◇	
	× 90.0	4,000	◇	◇	◇	
	× 100.0	4,000	◇	◇	◇	
	× 100.0	6,000	◇			
	× 125.0	4,000	◇	◇	◇	
	× 125.0	6,000	◇			
	× 150.0	4,000	◇	◇	◇	
× 150.0	6,000	◇				
× 200.0	4,000	◇	◇	◇		
× 250.0		◇	◇	◇		
× 300.0		◇	◇			
10.0	× 15.0		◇	◇	◇	
	× 19.0		◇	◇	◇	
	× 20.0		◇	◇	◇	◇
	× 25.0		◇	◇	◇	◇
	× 30.0		◇	◇	◇	◇
	× 32.0		◇	◇	◇	◇
	× 35.0		◇			
	× 38.0		◇	◇	◇	◇
	× 40.0		◇	◇	◇	◇

SUS304 平角棒

各種サイズ		表面状態				備考
寸法 (a × b mm)	長さ (mm)	HOT	COLD	HL	400番研磨	
10.0	× 45.0	4,000	◇			
	× 50.0		◇	◇	◇	◇
	× 60.0		◇			
	× 65.0		◇	◇	◇	◇
	× 75.0		◇	◇	◇	◇
	×100.0		◇	◇	◇	
	×125.0		◇	◇	◇	
	×150.0		◇	◇	◇	
	×200.0		◇	◇	◇	
	×250.0		◇	◇	◇	
	×300.0		◇	◇		
12.0	× 14.0			◇		
	× 15.0		◇			
	× 16.0			◇		
	× 19.0		◇	◇	◇	
	× 20.0		◇	◇	◇	◇
	× 25.0		◇	◇	◇	◇
	× 28.0		◇			
	× 30.0		◇	◇	◇	◇
	× 32.0		◇	◇	◇	◇
	× 32.0	6,000		◇	◇	
	× 35.0	4,000	◇	◇	◇	
	× 38.0		◇	◇	◇	◇
	× 38.0	6,000	◇	◇	◇	
	× 40.0	4,000	◇	◇	◇	◇
	× 40.0	6,000		◇	◇	
	× 45.0	4,000	◇	◇	◇	
	× 50.0		◇	◇	◇	◇
	× 50.0	6,000	◇	◇	◇	
	× 65.0	4,000	◇	◇	◇	◇
	× 65.0	6,000	◇	◇	◇	
	× 70.0	4,000	◇			
	× 75.0		◇	◇	◇	◇
	× 75.0	6,000	◇	◇	◇	
	× 90.0	4,000	◇	◇	◇	
	×100.0	4,000	◇	◇	◇	
	×100.0	6,000	◇			
	×125.0	4,000	◇	◇	◇	
	×125.0	6,000	◇			
	×150.0	4,000	◇	◇	◇	
	×150.0	6,000	◇			
×200.0	4,000	◇	◇	◇		
×250.0		◇	◇	◇		
×300.0		◇	◇			
16.0	× 19.0			◇		
	× 20.0		◇	◇	◇	◇
	× 25.0		◇	◇	◇	◇
	× 30.0		◇			
	× 32.0		◇	◇	◇	◇

SUS304 平角棒

各種サイズ		表面状態				備考
寸法 (a × b mm)	長さ (mm)	HOT	COLD	HL	400番研磨	
16.0	× 35.0	4,000	◇			
	× 38.0		◇	◇	◇	◇
	× 40.0		◇	◇	◇	
	× 45.0		◇			
	× 50.0		◇	◇	◇	◇
	× 50.0	6,000	◇			
	× 65.0	4,000	◇	◇	◇	
	× 65.0	6,000	◇			
	× 75.0	4,000	◇	◇	◇	
	× 75.0	6,000	◇			
	× 90.0	4,000	◇			
	× 100.0		◇	◇	◇	
	× 100.0	6,000	◇			
	× 125.0	4,000	◇	◇	◇	
	× 125.0	6,000	◇			
	× 150.0	4,000	◇	◇	◇	
	× 150.0	6,000	◇			
	× 200.0	4,000	◇	◇	◇	
	× 250.0		◇	◇	◇	
	× 300.0		◇	◇		
19.0	× 25.0		◇	◇	◇	◇
	× 30.0		◇			
	× 32.0		◇	◇	◇	◇
	× 35.0		◇			
	× 38.0		◇	◇	◇	◇
	× 40.0		◇			
	× 45.0		◇			
	× 50.0		◇	◇	◇	◇
	× 55.0		◇			
	× 65.0		◇	◇	◇	
	× 75.0		◇	◇	◇	
	× 90.0		◇			
	× 100.0		◇	◇	◇	
	× 125.0		◇	◇	◇	
	× 150.0		◇	◇	◇	
	× 200.0		◇	◇	◇	
× 250.0		◇	◇	◇		
× 300.0		◇	◇			
20.0	× 70.0		◇			
22.0	× 25.0		◇			
	× 30.0		◇			
	× 32.0		◇	◇		
	× 35.0		◇			
	× 38.0		◇	◇		
	× 40.0		◇			
	× 45.0		◇			
	× 50.0		◇	◇		
	× 65.0		◇	◇		
× 75.0		◇	◇			

SUS304 平角棒

各種サイズ		表面状態				備考
寸法 (a × b mm)	長さ (mm)	HOT	COLD	HL	400番研磨	
22.0	× 90.0	◇				
	× 100.0	◇	◇			
	× 125.0	◇				
	× 150.0	◇				
	× 200.0	◇				
	× 250.0	◇				
	× 300.0	◇				
25.0	× 32.0	◇	◇			
	× 38.0	◇	◇			
	× 40.0	◇				
	× 50.0	◇	◇			
	× 60.0	◇				
	× 65.0	◇	◇			
	× 75.0	◇	◇			
	× 100.0	◇	◇			
	× 125.0	◇	◇			
	× 150.0	◇	◇			
	× 200.0	◇	◇			
	× 250.0	◇	◇			
	× 300.0	◇	◇			
30.0	× 50.0	◇	◇			
	× 55.0	◇	◇			
	× 65.0	◇	◇			
	× 75.0	◇	◇			
	× 100.0	◇	◇			
	× 125.0	◇				
	× 150.0	◇				
	× 200.0	◇				
	× 250.0	◇				
	× 300.0	◇				
35.0	× 50.0	◇	◇			
	× 55.0	◇				
	× 65.0	◇	◇			
	× 75.0	◇	◇			
	× 100.0	◇	◇			
	× 125.0	◇				
	× 150.0	◇				
40.0	× 50.0	◇				
	× 65.0	◇				
	× 75.0	◇				
	× 100.0	◇				
	× 125.0	◇				
	× 150.0	◇				
50.0	× 65.0	◇				
	× 75.0	◇				
	× 100.0	◇				
	× 125.0	◇				
	× 150.0	◇				
60.0	× 75.0	◇				

◇ 手配品



SUS304 平角棒

各種サイズ		長さ (mm)	表面状態				備考
寸法 (a × b mm)			HOT	COLD	HL	400番研磨	
60.0	×100.0	4,000	◇				
	×125.0		◇				
	×150.0		◇				
65.0	×75.0		◇				
	×100.0		◇				
70.0	×100.0		◇				
	×125.0		◇				
	×150.0		◇				
80.0	×100.0		◇				
	×125.0		◇				
	×150.0		◇				
90.0	×100.0		◇				
	×125.0		◇				
	×150.0		◇				
100.0	×125.0		◇				
	×150.0	◇					