


伸銅品

# りん脱酸銅 C1220・C1201

▶ 比重 8.94




銅(Cu)99.90%以上、りん(P)0.015~0.040%を含む純銅。酸素量が少ないので水素脆化もなく、耐食性、耐候性、絞り加工性、熱伝導性(熱伝導率80%前後→りん(P)が伝導性を妨げる)に優れています。風呂釜、屋根板などに使用されています。



伸銅品

## りん脱酸銅 丸パイプ(C1220)



各種サイズ		長さ (mm)	調質			備考
寸法 (a × t mm)			H	1/2H	O	
2.0	× 0.3	2,000	◇			
	× 0.5		◇			
2.5	× 0.5		◇			
3.0	× 0.5	2,500	◇			
	× 0.6		◇			
	× 0.8		◇			
	× 1.0		◇			
3.18	× 0.5		◇			
	× 0.8		◇			
3.5	× 0.5		◇			
4.0	× 0.5			◇		
	× 0.5	4,000		◇		
	× 0.8	5,000		◇		
	× 1.0			◇		
4.76	× 0.8	5,000		◇		
5.0	× 0.5		◇			
	× 0.6		◇			
	× 0.8			◇		
	× 1.0			◇		
	× 2.5		◇			
6.0	× 0.5			◇		
	× 0.8			◇		
	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
6.35	× 0.8			◇		
	× 1.0			◇		
	× 1.5			◇		
7.0	× 1.0			◇		
	× 2.0			◇		
8.0	× 0.5			◇		
	× 0.8			◇		
	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		

◇ 手配品

▶ 注 16.0 × 1 以上 切断可

## りん脱酸銅 丸パイプ(C1220)

各種サイズ		長さ(mm)	調質			備考
寸法(a × t mm)			H	1/2H	O	
8.0	×2.0	5,000		◇		
9.0	×1.0			◇		
9.53	×0.8			◇		
	×1.0			◇		
	×1.2			◇		
	×1.5			◇		
10.0	×0.5			◇		
	×0.8			◇		
	×1.0			◇		
	×1.2			◇		
	×1.5			◇		
	×2.0			◇		
12.0	×1.0			◇		
	×1.2			◇		
	×1.5			◇		
	×2.0			◇		
	×3.0			◇		
12.7	×0.8			◇		
	×1.0		◇			
	×1.2		◇			
	×1.5		◇			
	×2.0		◇			
13.0	×1.0		◇			
14.0	×1.0		◇			
	×1.5		◇			
	×2.0		◇			
	×3.0		◇			
15.0	×1.0		◇			
	×1.2		◇			
	×1.5		◇			
	×2.0		◇			
15.88	×0.8		◇			
	×1.0		◇			
	×1.2		◇			
	×1.24		◇			
	×1.5		◇			
	×2.0		◇			
◇手配品 16.0	×1.0		◇			
	×1.2		◇			
	×1.5		◇			
	×2.0		◇			
	×3.0		◇			
	×4.0		◇			
18.0	×1.0		◇			
	×1.2		◇			
	×1.5		◇			
	×2.0		◇			
	×3.0		◇			

## りん脱酸銅 丸パイプ(C1220)

各種サイズ		長さ (mm)	調質			備考
寸法 (a × t mm)			H	1/2H	O	
19.05	× 1.0	5,000		◇		
	× 1.2			◇		
	× 1.5			◇		
	× 2.0			◇		
	× 3.0			◇		
20.0	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
	× 2.0			◇		
	× 3.0			◇		
	× 4.0		◇			
× 5.0		◇				
21.7	× 2.8			◇		
22.0	× 1.5			◇		
	× 2.0			◇		
	× 3.0			◇		
	× 4.0			◇		
	× 5.0		◇			
22.23	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
	× 1.65			◇		
	× 2.0			◇		
	× 3.0			◇		
25.0	× 1.0			◇		
	× 1.5			◇		
	× 2.0			◇		
	× 3.0			◇		
	× 5.0		◇			
25.4	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
	× 2.0			◇		
	× 3.0			◇		
27.2	× 2.8		◇			
28.0	× 1.5			◇		
	× 3.0			◇		
28.58	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
	× 1.65			◇		
	× 2.0			◇		
	× 3.0			◇		
30.0	× 1.5			◇		
	× 2.0			◇		
	× 2.5			◇		
	× 3.0			◇		
31.75	× 1.0			◇		
	× 1.2			◇		

◇手配品

▶注 16.0 × 1 以上 切断可

## りん脱酸銅 丸パイプ(C1220)

各種サイズ		長さ(mm)	調質			備考	
寸法(a × t mm)			H	1/2H	O		
31.75	× 1.5	5,000		◇			
	× 2.0			◇			
	× 3.0			◇			
32.0	× 2.0				◇		
	× 3.2				◇		
34.93	× 1.5				◇		
	× 1.65				◇		
35.0	× 2.0				◇		
	× 3.0				◇		
38.1	× 1.2				◇		
	× 1.5				◇		
	× 2.01				◇		
	× 3.01				◇		
40.0	× 2.0				◇		
	× 3.0				◇		
41.28	× 29.0				◇		
	× 30.0				◇		
42.7	× 3.5				◇		
44.45	× 2.0				◇		
	× 3.0				◇		
48.6	× 3.5				◇		
50.8	× 1.5				◇		
	× 2.0				◇		
	× 3.0				◇		
57.2	× 20.0			◇			
60.0	× 1.0			◇			
	× 1.5			◇			
	× 2.0			◇			
	× 3.0			◇			
63.5	× 2.0			◇			
	× 3.0		◇				
70.0	× 3.0		◇				
76.2	× 2.0		◇				
	× 3.0		◇				
80.0	× 3.0		◇				
101.6	× 3.0		◇				

▶注 16.0 × 1 以上 切断可

◇手配品