

オーステナイト系

SUS316L

▶ 比重 7.98

SUS316Lは極低炭素鋼で、SUS316の性質に耐粒界腐食性をもたせたステンレス鋼です。
『L』はLow Carbon(低炭素)を表し、耐食性・機械的性質はSUS316と遜色なく使用できます。



オーステナイト系

SUS316L 丸棒

各種サイズ		表面状態			備考	
直径(mm)	長さ(mm)	酸洗	ピーリング	ターニング		
8.0	4,000UP	◇				
9.0		◇				
10.0		◇				
12.0		◇				
13.0		◇				
14.0		◇				
15.0		◇				
16.0		◇				
18.0				◇		
19.0				◇		
20.0				◇		
22.0				◇		
24.0				◇		
25.0				◇		
26.0				◇		
28.0				◇		
30.0			◇			
32.0			◇			

◇ 手配品

SUS316L 丸棒

各種サイズ		表面状態			備考	
直径 (mm)	長さ (mm)	酸洗	ピーリング	ターニング		
34.0	4,000UP		◇			
35.0				◇		
36.0				◇		
38.0				◇		
40.0				◇		
42.0				◇		
44.0				◇		
45.0				◇		
46.0				◇		
48.0				◇		
50.0				◇		
55.0				◇		
60.0				◇		
65.0				◇		
70.0				◇		
75.0				◇		
80.0				◇		
85.0				◇		
90.0				◇		
95.0				◇		
100.0				◇		
110.0				◇		
120.0				◇		
130.0				◇		
140.0				◇		
150.0				◇		
160.0				◇		
170.0					◇	
180.0					◇	
190.0					◇	
200.0					◇	
210.0					◇	
220.0					◇	
230.0					◇	
240.0				◇		
250.0				◇		
260.0				◇		
280.0				◇		
300.0	3,000UP			◇		
350.0				◇		
400.0				◇		
420.0	2,000UP			◇		
450.0				◇		
480.0				◇		
500.0				◇		